



- NOTE: 1) HYDRO @ 390 PSIG. MIN.
 2) ALL NPT ARE SA-182-304 S.S.
 3) UHA-51 (e)(2) NO IMPACT TESTING.

SHELL / HEADS		.1875" SA-240-304 S.S. 2:1 S.E.	
JOGGLE - .159 OFFSET			
.1875" SA-240-304 S.S.			
M.A.W.P.	300 PSIG. @ 200 °F		
M.D.M.T.	-155 °F @ 300 PSIG.		
ASME SECTION VIII	DIV. 1, 2010 ADD 2011		
X-RAY:	RT-NO		
GALLONS:	30	WT.	137 LBS.
SERIAL NO.			
N.B. NO.			
16-VD-30-R		REV.	12-30-11
304 S.S.		DATE:	10-22-10
FOR: HANSON STANDARD			
VERT. AIR TANK			
SURFACE AREA = 14.7 SQ. FT.			
INSIDE: UNPAINTED - PASSIVATE			
OUTSIDE: BEAD BLAST & PASSIVATE			
CAD-"B" SIZED UNDER "STD"-SERIES			
BY: J.G.	SCALE: 1"=12"		
ROY E. HANSON JR. MFG.			
1600 E. WASHINGTON BLVD.			
LOS ANGELES, CA 90021			