



- NOTES:
- 1) HYDRO @ 260 PSIG. MIN.
 - 2) CRN SASKATCHEWAN
 - 3) IMPACT TESTED? NO UG-20(f)
 - 4) WELD SIZE NPT UW-16(f)(5)
 - 5) MANWAY RING EDGES MUST BE ROUNDED PER: UG-76(c)

SHELL / HEADS	
.166" SA-414-G 2:1 S.E.	
(.164"MIN.) JOGGLED-GREEN STRIPE	
.200" SA-455	
M.A.W.P. 200 PSIG. @ 200 °F	
M.D.M.T. -20 °F @ 200 PSIG.	
ASME. SECTION VIII DIV. 1, 2010 ADD 2010	
X-RAY: RT-NO	
GALLONS: 200	WT. 488 LBS.
SERIAL NO.	
N.B.	

0-30-VA-200-R	REV. 3-22-11
FOR: HANSON STANDARD	DATE: 5-23-94
VERT. AIR TANK	
SURFACE AREA = 50.2 SQ. FT.	
INSIDE: EPOXY LINED	
OUTSIDE: PRIME	
CAD-"B" SIZE UNDER "0"-SERIES	
BY: E.S.	SCALE: 1"=12"
ROY F. HANSON JR. MFG.	
1600 E. WASHINGTON BLVD.	
LOS ANGELES, CA 90021	