



NOTE: 1) HYDRO @ 260 PSIG. MIN.

SHELL / HEADS	
.166" SA-414-G	2:1 S.E.
(.164" MIN.) JOGGLE	
.149" OFFSET	
.175" SA-414-G	
(.174" MIN.)	
M.A.W.P.	200 PSIG. @ 200 °F
M.D.M.T.	-20 °F @ 200 PSIG.
ASME. SECTION VIII	DIV. 1, 2010 ADD 2010
X-RAY:	RT-4 SPOT L.S. ONLY
GALLONS:	240
WT.	559 LBS.
SERIAL NO.	
N.B.	

  

0-30-VA-240-R	REV. 3-22-11
FOR: HANSON STANDARD	DATE: 9-26-97
VERT. AIR TANK	
SURFACE AREA = 57.8 SQ. FT.	
INSIDE: EPOXY LINED	
OUTSIDE: PRIME	
CAD-"B" SIZE UNDER "O"-SERIES	
BY: E.S.	SCALE: 1"=12"
<b>ROY E. HANSON JR. MFG.</b>	
1600 E. WASHINGTON BLVD.	
LOS ANGELES, CA 90021	

1/4" THK. CLIPS PER MA-395-B (4) PLC'S. W/ 9/16" Ø HOLE ON 26 3/8" B.C.; WELD OUTSIDE VERT. EDGE OF CLIP ONLY