



NOTE: 1) HYDRO @ 260 PSIG. MIN.

SHELL / HEADS		.218" SA-455 2:1 S.E.	
JOGGLE - .249" OFFSET			
.248" SA-455			
M.A.W.P.	200 PSIG. @ 200 °F		
M.D.M.T.	-20 °F @ 200 PSIG.		
ASME. SECTION VIII DIV. 1, 2010 ADD 2010			
X-RAY:	RT-NO		
GALLONS:	400	WT.	920 LBS.
SERIAL NO.			
N.B.			
INSIDE: EPOXY LINED		SURFACE AREA = 81.2 SQ. FT.	
OUTSIDE: PRIME			
CAD-"B" SIZE UNDER "O"-SERIES			
BY: E.S.	SCALE: 3/4"=12"		
ROY E. HANSON JR. MFG.			
1600 E. WASHINGTON BLVD.			
LOS ANGELES, CA 90021			
FOR: HANSON STANDARD		REV. 3-22-11	
VERT. AIR TANK		DATE: 6-3-99	
0-36-VA-400-R			

1/4" THK. CLIPS PER MA-395-B (4) PLC'S. W/ 9/16" Ø HOLE ON 32 3/8" B.C.; WELD OUTSIDE VERT. EDGE OF CLIP ONLY