



- NOTE. 1 } HYDRO @ 215 PSIG. MIN.  
 2 } CRN SASKATCHEWAN  
 3 } IMPACT TESTED? NO UG-20 (f)  
 4 } MANWAY & PIPE INTERNAL EDGES SHALL BE ROUNDED.

SHELL / HEADS		.250" SA-455 2:1 S.E. (.243"MIN.) JOGGLED	
M.A.W.P. 165 PSIG. @ 400 °F		54-HM-1550-W	
M.D.M.T. -20 °F @ 165 PSIG.		REV. 8-17-11	
ASME SECTION VIII DIV. 1, 2010 ADD. 2010		DATE: 3-4-99	
X-RAY: RT-4 SPOT L.S.		FOR: HANSON STANDARD	
GALLONS: 1550 WT. 2624 LBS.		HORIZ. AIR TANK	
SERIAL NO.		SURFACE AREA = 210.0 SQ. FT.	
N.B.		UW-21 (b)	
		INSIDE: UNPAINTED	
		OUTSIDE: PRIME	
		CAD-"B" UNDER "STD"-SERIES	
		BY: J.G. SCALE: 1/2"=12"	
		<b>ROY E. HANSON JR. MFG.</b>	
		1600 E. WASHINGTON BLVD.	
		LOS ANGELES, CA 90021	

END VIEW W/O SUPPORTS